



CERTIFICATIONS:



WHO Certified



ISO-13485



EC60335-1



IEC-60335-2-24

SOUTH ZONE:

- Chennai** : Old No.14, New No. 47, 12th Avenue, Ashok Nagar, Chennai-600 083.
- Coimbatore** : Priya Ware House, No.52/1, Uzhalaipalar Street, Periyagounden, Thottam, Urumandampa layam, G.N. Mills Post, Coimbatore-641 029. Contact No. 9962566033.
- Cochin** : B.No: 2/378A, Methanam Road, Eloor North, Udyogamandal P.O. Kochi-683 501.
- Hyderabad** : D. No: 2 - 99, K.S.Towers, Vennelagadda, Besides Sarvothama Care, Near Suchitra Centre, Jedimetla (V), Hyderabad-500 055.
- Bangalore** : Survey 42/1, Katha No. 191/142/1, Haralukkute Village, Begur Hobli, Trio Apparels Compound, Hosapalya, Muneshwar Nagar, Kudlu Main Road, Bangalore-560 068.
- Vijaywada** : Door No.2-105/2, Kamakshi Godown, Nallagunta Centre, Gollapudi, Vijayawada Rural, Krishna Dist., AP-521 225.
- Vizag** : Served from Vijaywada.
- Hubli** : C/O -Madhuban Industries, Plot No. 117, 179 Rayapur Industrial Area, Behind Navalur Railway Goods Shed, Dharwad-580 009 (Karnataka)

EAST ZONE

- Kolkata** : 19A Jawaharlal Nehru Road, 3rd Floor, Flat No. D/1, Kolkata-700 087.
- Bhubaneswar** : C/O-Lingaraj Body Building Works, Plot No-1143, Near U.G.M.E School, At Hanspal, PS-Mancheswar, Bhubaneswar-752 101 (ODISHA).
- Patna** : S S Vihar, 4th Floor, Flat No.107, Station Road, Karbigahiya, Beside Bhagawati Complex and Ram Dulari Hotel, Patna-800 001.
- Guwahati** : 1st Floor, Upasana Palace Complex, R P Road, Ganeshguri, Guwahati, Kamrup Metropolitan Guwahati - 781 006, Assam.
- Ranchi** : Lower Chutia, Samlong, Ranchi, Jharkhand-834 001.
- Chattisgarh** : Acharya Nanesh Marg, D-272 M.R. Colony Tagore Nagar Square, Raipur-492 001 (CG)

WEST ZONE:

- Mumbai RO** : 7B Pannalal Silk Mills Compound, 78 LBS Marg, Bhandup (W), Mumbai, Maharashtra.
- Mumbai HO** : 501-505, 05th Floor, Ascot Centre, Sahar Road, Beside Hotel Hilton, Andheri (East), Mumbai-400 099
- Pune** : 2163/26, Manas Building, Near Nilayam theatre, Sadashiv Peth, Pune-411 030.
- Nashik** : Bilvadal Bungalow, Gaikwad Mala, Near Jain Bhavan, Nasik Road, Pin-422 101.
- Nagpur** : Plot No. 54, Veer Sawarkar Nagar, Near Chhatrapati Square, Nagpur-440 015.
- Ahmedabad** : 203, ABC -II, Opp. Wagh Bakri Tea Lounge, Near St. Xavier College Corner, Off CG Road, Navrangpura, Ahmedabad-380 009.
- Rajkot** : Served From Ahmedabad.
- Goa** : Shop No. 1 & 2, Ground Floor, Bearing S.V.No. 82/4, Mercurim, Agassaim-403 204, Goa.
- Indore** : Plot No.160 PU 4 Scheme No. 54, A.B. Road, Indore-452 001.
- Vapi** : Contact No. 7567533958

NORTH ZONE:

- Delhi** : Unit No. GH-1, Ground Floor, Vardhman Grand Plaza, Manglam Place, Sector-3, Rohini, Delhi-110 085.
- Jaipur** : Hall Mark, Special ("F"), Road No. 1, Industrial Estate 22 Godam, Jaipur, Rajasthan-302 006.
- Lucknow** : Ho. No. 610/2395 (533a) Faizullahganj - 3, Keshav Nagar, Sitapur Road, Lucknow (U.P)-226 021.
- Ludhiana** : 4222/1, Bent Pura, Chandigarh Road, Behind Sictech Computer, Ludhiana-141 010.
- Chandigarh** : Near Hotel KK Residency Shop No. 1, House No. 213 Sector 52, Village-Kajheri Chandigarh (U.T)-160 047.
- Jammu** : Birpur, Purmandal Road, Samba Jammu-181 133 (INDIA).



RELIABLE SERVICE

Our extensive service network ensures swift service and maintenance for all Western Equipment.

Call us at : **70450 17000**



COMPLETE SALES SUPPORT

With 25 branches across India, we're here to fulfill all your refrigeration needs.

Reach out at : **022 6907 0000**

PRESERVING HEALTH, ENSURING CARE

WESTERN'S MEDICAL REFRIGERATORS



www.westernequipments.com

Follow us on: [f](#) [@](#) [in](#)

WESTERN'S MEDICAL REFRIGERATORS



Vaccine Freezer: VFW140H-HC

Model	VFW140H-HC
External Dimensions (WDXH)	710(W) X 720(D) X 955(H)
Current (A)	0.90 Amp
Power Supply	Single phase, 220-240V AC, 50Hz
Effective Capacity	142 Ltr.
Vaccine Capacity	68 Ltr.
Refrigerant	R-290 Eco-friendly
Temp. Controller	Electronic Controller
Operating Condition	+5°C to +43°C
No. of Baskets	4 Nos.
Energy Consumption At 43°C	1.94kwh / 24 hrs.
Safe Temperature Range	-15°C to -25°C
Minimum Hold Over Time	3 hrs 33 mins
Max Vaccine Storage Capacity (Ltr.)	68 Ltr.
Max Water Pack Freezing Capacity (Ltr.)	16.2 Ltr. / 24hrs
Insulation Foam Blowing Agent	Cyclopentane



WHO PQS E003/127



Low Energy Consumption



Reliable International brand compressor with wide voltage



Copper evaporator coil



SS304 internal cabinet for rust-free life



Controller with 72hr display backup, high-temp alarm



Rugged adjustable leg (92-110mm)



High ICE Pack Freezing capacity



Long Hold Over Time with 80mm PU foam walls



Power cord with Anti-rodent conduit pipes



Vaccine Freezer: VFW310H-HC

Model	VFW310H-HC
External Dimensions (WDXH)	1230(W) X 720(D) X 965(H)
Current (A)	1.20 Amp
Power Supply	Single phase, 220-240V AC, 50Hz
Effective Capacity	317 Ltr.
Vaccine Capacity	166 Ltr.
Refrigerant	R-290 Eco-friendly
Temp. Controller	Electronic Controller
Operating Condition	+5°C to +43°C
No. of Baskets	8 Nos.
Energy Consumption At 43°C	2.27kwh / 24 hrs.
Safe Temperature Range	-15°C to -25°C
Minimum Hold Over Time	4 hrs.
Max Vaccine Storage Capacity (Ltr.)	166 Ltr.
Max Water Pack Freezing Capacity (Ltr.)	28.2 Ltr. / 24hrs
Insulation Foam Blowing Agent	Cyclopentane



WHO PQS E003/128



Low Energy Consumption



Reliable International brand compressor with wide voltage



Copper evaporator coil



SS304 internal cabinet for rust-free life



Controller with 72hr display backup, high-temp alarm



Rugged adjustable leg (92-110mm)



High ICE Pack Freezing capacity



Long Hold Over Time with 80mm PU foam walls



Power cord with Anti-rodent conduit pipes



Ice Lined Refrigerator: I425H120

Model	I425H120
External Dimensions (WDXH)	1320(W) X 805(D) X 970(H)
Current (A)	1.10 Amp
Power Supply	Single phase, 220-240V AC, 50Hz
Effective Capacity	253 Ltr
Vaccine Capacity	192 Ltr
Refrigerant	R-290 Eco-friendly
Temp. Controller	Electronic controller
Operating Condition	+10°C to +43°C
Energy Consumption At 43°C	1.50 kwh/24hrs
Safe Temperature Range	+2°C to +8°C
Minimum Hold Over Time	42 hrs 30 mins
Max Vaccine Storage Capacity (Ltr.)	192 Ltr.




WHO PQS E003/133



Low Energy Consumption



Reliable International brand compressor with wide voltage



Copper evaporator coil



SS304 internal cabinet for rust-free life



Controller with 72hr display backup, high-temp alarm



Rugged adjustable leg (92-110mm)



Maintenance-free condenser



Long Hold Over Time with 140mm PU foam walls



Power cord with Anti-rodent conduit pipes



Pharmaceutical Refrigerator: PR-600

Model	PR-600
External Dimensions (WDXH)	660(W) X 800(D) X 1949(H)
Current (A)	1.0 Amp
Power Supply	Single phase, 230V AC, 50Hz
Gross Volume	507 Ltr.
Refrigerant	R-290 Eco-friendly
Temp. Controller	"Electronic Controller (Touch Screen, 30 Day Data Storage, USB Download Option, Buzzer Alarm, Battery Back Up For Temperature Display)"
Operating Condition	+5°C to +43°C
No. of Shelves	4 Nos.
Energy Consumption At 32.2°C & 65% RH	1.23 Kwh / 24 hrs.
Safe Temperature Range	+2°C to +8°C
Options	Stain-less Steel Shelves
Insulation Foam Blowing Agent	Cyclopentane



Low Noise



Powerful cooling



Reliable International brand compressor with wide voltage



SS304 internal cabinet for rust-free life



Digital Temperature Display Indicator



Power cord with Anti-rodent conduit pipes



Best-in-class electronic motors



Maintenance-free condenser



Cleanable and replaceable antifungal-grade magnetic gasket